

DC VOLTAGE METER

Application:

The panel meter is suitable for measuring the DC voltage.

Important features:

- Full digital operation (Icom System).
- LED display range: ± 9999 .
- Preset delivery or connecting to external device can be set (monlcom option).
- Automatic zero calibration.
- Plug in terminal blocks with screw.
- EMC compliance.



Illustration only.

Technical specifications:

Input:

- Nominal input voltage range: from $0 \dots \pm 0.06$ V to $0 \dots \pm 600$ V DC
- Input measuring range: up to 120 % of the nominal value
- Input resistance: 1 Mohm
- Input insulation voltage: Cat. III. 1 kV (Test: $4300 V_{eff}$ 1 min)


Display:

- Display colours: red (basic version), yellow, green LED
- Height of digits: 9 mm
- Display update: 2 /s
- Accuracy: ± 0.2 % FS, ± 1 digit (20 %..120 % input range)

Other:

- Standards applied: IEC/EN 61010-1, IEC/EN 61326
- Auxiliary supply consumption: max. 2 W
- Wire cross-section of terminals: max. 2.5 mm^2
- Working temperature: $-10 \dots +25 \dots +60$ °C
- Temperature coefficient: max. 100 ppm/°C
- Warm-up time: 15 min
- Storage temperature: $-40 \dots +80$ °C
- Humidity: max. 85 %
- Vibration (acceleration): max. 2 g
- Dimension (HxWxD): 24 mm x 48 mm x 78 mm
- Case protection: from the front IP 40, from behind IP 20
- Case material: PC-GF
- Weight: approx. 0.2 kg

Connection diagram:




DC VOLTAGE METER

Auxiliary Supply variations:

5 V, 12 V, 24 V, 48 V DC $\pm 50\%$, converter
 9...28 V DC

(Voltage / Insulation) / 1 kV
 / not isolated from display

Isolation scheme:



Ordering examples: (Input; Display: range, unit, colour; Auxiliary Supply)

CD40-48v-VDC _ Input: 0... ± 110 V DC _ Display: 0... ± 100.0 kV, red _ Aux: 24 V DC converter
 CD40-48v-VDC _ Input: 0... ± 500 V DC _ Display: 0... ± 500.0 V, green _ Aux: 9...28 V DC (not isolated)

On request for extra charge special ranges (Input, Display, Auxiliary Supply) are possible.

Outline and cut-out dimensions:

