

# CD40-96p-ADC

## DC CURRENT METER

### **Application:**

The panel meter is suitable for measuring the DC current.

### **Important features:**

- Full digital operation (lcom System).
- LED display range: ± 9999, unit marking by LED.
- Preset delivery or connecting to external device can be set (monlcom option).
- Automatic zero calibration.
- Plug in terminal blocks with screw.
- EMC compliance.



Illustration only.

### **Technical specifications:**

#### **Input:**

- Nominal input current range: ..... from 0...±0.02 A to 0...±5 A DC
- Input measuring range: ..... up to 120 % of the nominal value
- Input drop out voltage: ..... 60 mV (at nominal current)
- Input insulation voltage: ..... Cat. III. 1 kV (Test: 4300 V<sub>eff</sub> 1 min)


#### **Display:**

- Display colours: red (basic version), orange, yellow, green, blue, white LED
- Height of digits: ..... 14 mm
- Brightness control: ..... via dimming input on rear (optional)
- Dimmer input signal: ..... 5V PWM, approx. 1 kHz
- Dimmer input isolation: ..... Cat. III. 1 kV (Test: 4300 V<sub>eff</sub> 1 min)
- Display update: ..... 2 /s
- Accuracy: ..... ±0.2 % FS, ±1 digit (20 %..120 % input range)

#### **Other:**

- Standards applied: ..... IEC/EN 61010-1, IEC/EN 61326
- Auxiliary supply consumption: ..... max. 2 W
- Wire cross-section of terminals: ..... max. 2.5 mm<sup>2</sup>
- Working temperature: ..... -10...+25...+60 °C
- Temperature coefficient: ..... max. 200 ppm/°C
- Warm-up time: ..... 15 min
- Storage temperature: ..... -40...+80 °C
- Humidity: ..... max. 85 %
- Vibration (acceleration): ..... max. 2 g
- Dimension (HxWxD): ..... 48 mm x 96 mm x 74 mm
- Case protection: ..... from the front IP 40, from behind IP 20
- Case material: ..... PC-GF
- Weight: ..... approx. 0.3 kg

### **Connection diagram:**




# CD40-96p-ADC

## DC CURRENT METER

### Auxiliary Supply variations:

(Voltage / Insulation)	
5 V, 12 V, 24 V, 48 V DC ±50 %, converter	/ 1 kV
55...264 V, 47...440 Hz, and 72...370 V DC, converter	/ 3 kV
9...28 V DC	/ not isolated from display

### Isolation scheme:



**Ordering examples:** (Input; Display: range, unit, colour; Auxiliary Supply)

CD40-96p-ADC \_ Input: 0...±5 A DC \_ Display: 0...±10.00 kA, red \_ Aux: 55..264 V AC converter  
 CD40-96p-ADC \_ Input: 0...±1 A DC \_ Display: 0...±50.00 A, green, dimmable \_ Aux: 24 V DC converter

On request for extra charge special ranges (Input, Display, Auxiliary Supply) are possible.

### Outline and cut-out dimensions:

