

7.000 VAC  
9.000 VDC



Technical data	<b>F1-1B / F1-1N</b>
Test voltage:	200 .. 3.500 VAC 300 .. 7.000 VAC 300 .. 4.500 VDC (option) 400 .. 9.000 VDC (option)
Nominal power:	500 VA
Tripping current:	0 .. 1 / 10 / 70 mA
Interface:	RS232-C
Mains voltage:	230 V / ±10% / 49 .. 51 Hz*
Size:	19" / 4 HU
Weight:	approx. 23 kg



Front view F1-1B



Front view F1-1N



Rear view F1-1B, F1-1N

### Modular high-voltage testing device

Device versions with different output voltages are available depending on the application. The optional extension modules allow individual configuration of your system. For more detailed technical data, please see the table on back.

	Description	Size	Article no.
High-voltage test device	incl. TouchMe control unit	19" / 4 HU	F1-1B
High-voltage test device	for automatic use	19" / 4 HU	F1-1N

### Extension modules for the test devices

	Technical data	For device type	Article no.
DC voltage	Test voltage: 300 .. 4.500 / 9.000 VDC Tripping current: 0 .. 1 / 10 / 70 mA	F1-1B, F1-1N	F1-1B E01
Insulation resistance	0.1 .. 1 / 10 / 35 MΩ + Autorange	F1-1B, F1-1N	F1-1B E02
Security current limitation	< 3 mA for AC; < 5 mA for DC	F1-1B, F1-1N	F1-1B E03
Voltage feedback	The module allows a four-wire measurement by readback of the test voltage. Two high-voltage sockets are additionally incorporated in the back panel of the device.	F1-1B, F1-1N	F1-1B E04
Burn-Mode	Overvoltage tripping can be deactivated for troubleshooting.	F1-1B, F1-1N	F1-1B E05
Digital additional outputs	Six additional digital outputs for activation of an external switching matrix.	F1-1B, F1-1N	F1-1B E06
Ethernet	Alternative interface to RS232-C	F1-1B, F1-1N	F1-1B E10
USB	Alternative interface to RS232-C	F1-1B, F1-1N	F1-1B E12
Software package	ElutionDevice software package	F1-1B, F1-1N	N2-1A Z7D
Device driver	On request		
Calibration	Supplied with Elabo works calibration protocol	F1-1B, F1-1N	F1-1B E99

The description of the accessories can be found starting on page 108.

Please also see our sample configurations starting on page 36.

\*other mains frequency on request

Technical specifications subject to change without notice.

# 7.000 VAC 9.000 VDC

Device	F1-1B	F1-1N
<b>Application fields</b>		
Automatic use	●	●
Manual use	●	
<b>Operation</b>		
Touch Display 6.5"	●	
Interface	●	●
Start button	●	
Reset button	●	●
<b>Interfaces</b>		
RS 232-C	●	●
Ethernet	○	○
USB	○	○
USB accessory interface	●	
Digital interface 1	●	●
Digital interface 2	○	○
2 safety circuits	●	●
<b>Connections</b>		
HV test probes, rear	●	●
HV test probes, front	●	●
Warning lights	●	●
Non-heating apparatus socket	●	●
<b>Test functions</b>		
High voltage AC	●	●
High voltage DC	○	○
Insulation resistance measurement	○	○
Current limitation (EN50191) <sup>1</sup>	○	○
Burn-Mode (deact. tripping) <sup>1</sup>	○	○
Voltage feedback	○	○
<b>Test voltages</b>		
Test voltage AC 1	200 .. 3.500 V	
Test voltage AC 2	300 .. 7.000 V	
Test voltage DC 1 <sup>2</sup>	300 .. 4.500 V	
Test voltage DC 2 <sup>2</sup>	400 .. 9.000 V	
Residual ripple DC <sup>2</sup>	< 3 % bei R > 3 MΩ	
Positioning rate for ramp	10 .. 3.500 V/s	
Adjustment inaccuracy	Typ. 15 V	
Measurement error, voltage	1% of meas. ± 2 digit	
<b>Current ranges</b>		
Measurement range 1 / resolution	0 .. 70 mA / 100 μA	
Measurement range 2 / resolution	0 .. 10.0 mA / 10 μA	
Measurement range 3 / resolution	0 .. 1.000 mA / 1 μA	
Current tripping	Active current – Apparent current – Crest value – Delta I	
Accuracy	measurement range 1	0.5 % of meas. +/- 2 digit
	measurement range 2	0.5 % of meas. +/- 5 digit
	measurement range 3	0.5 % of meas. +/- 20 digit
Apparent current	measurement range 1	1.0 % of meas. +/- 5 digit
	measurement range 2	1.0 % of meas. +/- 5 digit
	measurement range 3	1.0 % of meas. +/- 20 digit
Accuracy Peak value	measurement range 1	1.0 % of meas. +/- 8 digit
	measurement range 2	1.0 % of meas. +/- 8 digit
	measurement range 3	1.0 % of meas. +/- 20 digit
Active current	measurement range 1	0.5 % of meas. +/- 2 digit
	measurement range 2	0.5 % of meas. +/- 2 digit
	measurement range 3 <sup>2</sup>	0.5 % of meas. +/- 2 digit
Accuracy DC	measurement range 1 <sup>2</sup>	0.5 % of meas. +/- 2 digit
	measurement range 2 <sup>2</sup>	0.5 % of meas. +/- 2 digit
	measurement range 3 <sup>2</sup>	0.5 % of meas. +/- 2 digit
<b>Insulation resistance measurement<sup>2</sup></b>		
Test voltage DC 1	300 .. 4.500 V	
Test voltage DC 2	400 .. 9.000 V	
Measurement range 1	0.1 .. 1.00 MΩ	
Measurement range 2	1 .. 10.0 MΩ	
Measurement range 3	10 .. 35 MΩ	
Autorange	0.1 .. 35 MΩ	
Accuracy at 500 V	3% of meas. ± 1 digit	
Accuracy at 1.000 V	1% of meas. ± 1 digit	



Flexibility is of prime importance with Elabo. That is why two versions of the devices in this line of equipment are available. Depending on the purpose, universal use or fully automated operation are possible.

### Technical main data

Nominal power	500 VA
Short-circuit current	>140 mA
Mains voltage	230 V +/- 10%
Mains frequency	49 .. 51 Hz*
Dimensions Depth 360 mm	19" / 4 HU
Weight	23 kg   22 kg
Permissible relative humidity	25 .. 75 % rel.
Operating temperature	10 .. 50 °C
Test time	0.1 .. 999.9 s constant testing
Burn-Mode current <sup>2</sup>	ca. 140 mA
Feedback threshold <sup>2</sup>	0.7 .. 1 x U <sub>test</sub>

- Standard ○ Optional

<sup>1</sup> cannot be combined

<sup>2</sup> Extension module required

\*other mains frequency on request

Technical specifications subject to change without notice.